

# 2026 OUTLANDER DPS



### PACKAGE HIGHLIGHTS

- Tri-Mode Dynamic Power Steering (DPS™)
- Visco-Lok<sup>†</sup> QE auto-locking front differential
- 25 in. tires with 12 in. steel wheels
- Full skid plate
- Glove box
- Front drop-down storage

| ENGINES              | 500  | 700   |
|----------------------|--|---|
| Type                 | 40 hp / 37 lb-ft, Rotax® ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid-cooled | 50 hp / 41 lb-ft, Rotax ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid-cooled |
| Fuel Delivery System | Electronic Fuel Injection (EFI)  |   |
| Transmission         | pDrive primary CVT L / H / N / R / P   |   |
| Drive Train          | Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential                               |   |
| Driving Assistance   | N/A  | Work / Standard / Sport modes   |
| Power Steering       | Tri-Mode Dynamic Power Steering (DPS)  |   |

| SUSPENSIONS      |  |
|------------------|--|
| Front Suspension | Double A-arm 9.75 in. (24.8 cm) travel |
| Front Shocks     | Twin-tube                              |
| Rear Suspension  | Double A-arm 10.25 in. (26 cm) travel  |
| Rear Shocks      | Twin-tube                              |

| TIRES & WHEELS     |                    |
|--------------------|--------------------|
| Front / Rear Tires | 25 x 8/10 x 12 in. |
| Wheels             | 12 in. steel       |

| BRAKES |   |
|--------|---|
| Front  | Dual 214 mm disc brakes with hydraulic twin-piston calipers |
| Rear   | Single 214 mm disc brake with hydraulic twin-piston caliper |

| DIMENSIONS & CAPACITIES |  |
|-------------------------|--|
| Estimated Dry Weight*   | 750 lb (340.2 kg)                                |
| L x W x H               | 86.7 x 47.6 x 48 in. (220.2 x 120.9 x 122 cm)    |
| Wheelbase               | 53 in. (134.5 cm)                                |
| Ground Clearance        | 12 in. (30.5 cm)                                 |
| Seat Height             | 38 in. (96.7 cm)                                 |
| Rack Capacity           | Front: 120 lb (54.4 kg)<br>Rear: 240 lb (109 kg) |
| Storage Capacity        | 9 gal (34 L)                                     |
| Towing Capacity         | 1,830 lb (830 kg)                                |
| Fuel Capacity           | 5.1 gal (19.5 L)                                 |

| FEATURES        |                               |
|-----------------|-------------------------------|
| Gauge           | 4.5 in. digital display       |
| Magneto         | 500 W                         |
| Instrumentation | N/A                           |
| Ignition        | Mechanical key                |
| Lighting        | LED headlights and taillights |
| Winch           | N/A                           |
| Seat            | Standard                      |
| Handlebar       | Standard                      |
| Protection      | Full skid plate               |
| Hitch Type      | 2 in. hitch receiver          |

| WARRANTY & EXTENDED SERVICE |   |
|-----------------------------|---|
| Factory Warranty            | 1-year BRP limited warranty             |
| Extended Service Terms      | B.E.S.T. term available up to 36 months |



© 2025 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. \*Base model dryweight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in the U.S.A. call the ATV Safety Institute at 1-800-887-2887. In Canada, call the Canadian Safety Council at 1-613-739-1535, ext 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding, alcohol and drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90 cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

