## **2026 OUTLANDER PRO**



## PACKAGE HIGHLIGHTS

- Visco-Lok<sup>†</sup> auto-locking front differential
- 26 in. 6-ply rating tires
- · Heavy-duty front bumper, rear bumper, full skid plate
- Glove box
- Front drop-down storage

ENGINES	HD5	HD7
Туре	40 hp / 37 lb-ft, Rotax® ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid-cooled	50 hp / 41 lb-ft, Rotax ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid-cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)	
Transmission	pDrive primary CVT with work calibration Extra low L / H / N / R / P	
Drive Train	Selectable 2WD / 4WD with Visco-Lok auto-locking front differential	
Driving Assistance	Speed limiter	Work / Standard / Sport modes Intelligent Engine Braking (iEB <sup>TM</sup> ) Speed limiter
Power Steering	N/A	
SUSPENSIONS		
Front Suspension	Double A-arm 9.75 in. (24.8 cm) travel	
Front Shocks	Twin-tube	
Rear Suspension	Double A-arm 10.25 in. (26 cm) travel	
Rear Shocks	Twin-tube	
TIRES & WHEELS		
Front / Rear Tires	6-ply rating 26 x 8/10 x 12 in.	
Wheels	12 in. steel	
BRAKES		
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers	
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper	

Estimated Dry Weight*	800 lb (362.9 kg)	
LxWxH	89.9 x 48.8 x 48.2 in. (228.4 x 123.9 x 122.5 cm)	
Wheelbase	53 in. (134.5 cm)	
Ground Clearance	13 in. (33 cm)	
Seat Height	38.6 in. (98 cm)	
Rack Capacity	Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg)	
Storage Capacity	9 gal (34 L)	
Towing Capacity	1,830 lb (830 kg)	
Fuel Capacity	5.1 gal (19.5 L)	
FEATURES		
Gauge	4.5 in. digital display	
Magneto	420 W	
Instrumentation	N/A	
Ignition	RF Digitally Encoded Security System (D.E.S.S.™)	
Lighting	LED headlights and taillights	
Winch	N/A	
Seat	Standard	
Handlebar	Standard	
Protection	Heavy-duty front bumper Rear bumper HMWPE front and rear A-arm protection (5 mm) Full skid plate	
Hitch Type	2 in. hitch receiver	
WARRANTY & EXTE	INDED SERVICE	
Factory Warranty	1-year BRP limited warranty	
Extended Service Terms	B.E.S.T. term available up to 36 months	



