

2026 OUTLANDER MAX ELECTRIC



White
Granite Grey

PACKAGE HIGHLIGHTS

- Liquid-cooled system: Battery, inverter, motor and on-board charger
- Charging from 20% to 80% in as little as 50 min
- Up to 50 miles (80 km) of range
- High and Low gears allow full work capacity
- Engine modes and speed limiter
- Dedicated tires for optimal noise and vibration level
- 3-level regen braking
- On-the-fly reverse capabilities
- 5 in. colored display
- Front and rear bumpers
- LED headlights and taillights, specific LED POD light

MOTOR

Type	47 hp / 53 lb-ft, ROTAX® E-POWER, Liquid-cooled
Power	Peak: 47 hp (35 kW) Continuous: 27 hp (20 kW)
Torque Motor	Peak: 53 lb-ft (72 Nm) Continuous: 21 lb-ft (28 Nm)
Top Speed	High gear: 50 mph (80 km/h) Low gear: 28 mph (45 km/h)

BATTERY

Battery Type	Integrated, lithium-ion
Battery Operating Temperature Range	From -20°C to 40°C (-4 Fahrenheit to 104 Fahrenheit)
Battery Capacity	8.9 kWh
Cooling System	Liquid-cooled: Battery, inverter and on-board charger Integrated AC heater for charging at low temperature
Estimated Range (when fully charged)	Tested in accordance with WMTC*: 50 miles (80 km) Average utility range*: 31 miles (50 km)
Feature	Regen braking with 3 levels of adjustment
Charger	On-board charger 6.6 kW Level 2 (compatible with level 1 charging)
Connector Type	Type 1 J1772 with integrated LED light
Charging Time Level 2 (240 V)	50 min (20–80%) 1 hour 30 min (0–100%)
Charging Time Level 1 (120 V)	3 hours 10 min (20–80%) 5 hours 15 min (0–100%)

DRIVETRAIN

Transmission	L / N / H / P Reverse activated via start button
Drive Train	Selectable 2WD / 4WD with Visco-Lok [†] QE auto-locking front differential
Driving Assistance	Work / Standard / Sport modes Speed limiter
Power Steering	Tri-Mode Dynamic Power Steering (DPS™)

SUSPENSIONS

Front Suspension	Double A-arm 9.75 in. (24.8 cm) travel
Front Shocks	Twin-tube
Rear Suspension	Double A-arm 10.25 in. (26 cm) travel
Rear Shocks	Twin-tube

TIRES & WHEELS

Front / Rear Tires	XPS Recon Force 26 x 8/10 x 14 in.
Wheels	14 in. cast-aluminum

BRAKES

Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper

DIMENSIONS & CAPACITIES

Estimated Dry Weight**	915 lb (415kg)
L x W x H	94.2 x 47.6 x 54 in. (239.2 x 120.9 x 137.1 cm)
Wheelbase	60.4 in. (153.5 cm)
Ground Clearance	12 in. (30.5 cm)
Seat Height	38.6 in. (98 cm)
Rack Capacity	Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg)
Storage Capacity	9 gal (34 L)
Towing Capacity	1,830 lb (830 kg)

FEATURES

Gauge	5 in. colored display
DC-DC Converter	Continuous 500W (at all speeds including at idle)
Instrumentation	Phone charger with 1xUSB-A and 1xUSB-C outputs
Ignition	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	LED headlights and taillights LED signature LED POD light
Winch	N/A
Seat	Removable passenger's seat
Handlebar	Standard
Protection	Front and rear bumpers Full skid plate
Hitch Type	2 in. hitch receiver

WARRANTY & EXTENDED SERVICE

Factory Warranty	Battery: 5 years (12,427 miles / 20,000 km limit) Motor: 1-year Vehicle: 1-year BRP limited warranty
------------------	--



© 2025 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. *WMTC: World Motorcycle Test Cycle. **Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in the U.S.A. call the ATV Safety Institute at 1-800-887-2887. In Canada, call the Canadian Safety Council at 1-613-739-1535, ext 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding, alcohol and drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90 cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

