2026 OUTLANDER MAX DPS



PACKAGE HIGHLIGHTS

| 850 | 1000R |
|---|--|
| Tri-Mode Dynamic Power Steering (DPS™) | 850 package highlights plus 1000R exclusive features: |
| Intelligent Engine Braking (iEB™) and driving modes | Specific CVT calibration High flow radiator cooling fan of |

- Radiator cooling fan of 80W & 150 cm3
- Visco-Lok† QE auto-locking front differential
- 26 in. tires with 12 in. aluminum wheels
- 7.6 in. wide digital display
- Full skid plate
- Front drop-down storage
- Rear removable storage
- · Phone storage

- High flow radiator cooling fan of 120W & 500 cm³
- 4-disc braking system
- 14 in. aluminum wheels
- LED signature lights

| 850 | 1000R |
|---|--|
| 82 hp / 66 lb-ft, Rotax* 999 cc V-twin, DOHC, liquid-cooled Radiator cooling fan of 80W & 150 cm³ | 101 hp / 69 lb-ft, Rotax 999 cc V-twin, DOHC, liquid-cooled High flow radiator cooling fan of 120W & 500 cm ³ |
| Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI) | |
| pDrive primary CVT L / H / N / R / P | pDrive primary CVT with specific calibration L/H/N/R/P |
| Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential | |
| Work / Standard / Sport modes Intelligent Engine Braking (iEB) | |
| Tri-Mode Dynamic Power Steering (DPS) | |
| | |
| Arched double A-arm 10.8 in. (27.4 cm) travel | |
| Twin-tube | |
| Arched double A-arm 12 in. (30.5 cm) travel | |
| Twin-tube | |
| | |
| 26 x 8/10 x 12 in. | 26 x 8/10 x 14 in. |
| 12 in. aluminum | 14 in. aluminum |
| | |
| Dual 214 mm disc brakes with hydraulic twin-piston calipers | |
| Single 214 mm disc brake with hydraulic twin-piston caliper | Dual 214 mm disc brakes with hydraulic twin-piston calipers |
| | 82 hp / 66 lb-ft, Rotax* 999 cc V-twin, DOHC, liquid-cooled Radiator cooling fan of 80W & 150 cm³ Intelligent Throttle Control (iT with Electronic Fuel Injection pDrive primary CVT L / H / N / R / P Selectable 2WD / 4WD with Visco-Lok QE auto-locki Work / Standard / Sport mod Intelligent Engine Braking (iEl Tri-Mode Dynamic Power Ste Arched double A-arm 10.8 in. (27.4 cm) travel Twin-tube Arched double A-arm 12 in. (30.5 cm) travel Twin-tube 26 x 8/10 x 12 in. 12 in. aluminum Dual 214 mm disc brakes with Single 214 mm disc brakes with Single 214 mm disc brakes with Single 214 mm disc brakes with |

| DIMENSIONS & CAPACITIES | 850 | 1000R |
|---------------------------|--|--|
| Estimated Dry Weight* | 967 lb (439 kg) | · |
| LxWxH | 94.8 x 48.5 x 56.4 in. (240.8 x 123.2 x 143.2 cm) | |
| Wheelbase | 60.8 in. (154.4 cm) | |
| Ground Clearance | 11.5 in. (29.2 cm) | |
| Seat Height | 37.8 in. (96 cm) | |
| Rack Capacity | Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg) | |
| Storage Capacity | 10.6 gal (40 L) | |
| Towing Capacity | 1,830 lb (830 kg) | |
| Fuel Capacity | 5.1 gal (19.5 L) | |
| FEATURES | | |
| Gauge | 7.6 in. wide digital display | |
| Magneto | 650 W | |
| Instrumentation | Phone storage | |
| Ignition | RF Digitally Encoded Security System (D.E.S.S.™) | |
| Lighting | LED headlights and taillights | LED headlights and taillights LED signature |
| Winch | N/A | |
| Seat | Removable passenger seat | |
| Handlebar | Standard | |
| Protection | Full skid plate | |
| Hitch Type | 2 in. hitch receiver | |
| WARRANTY & EXTER | NDED SERVICE | |
| Factory Warranty | 1-year BRP limited warranty | |
| Extended Service Terms | B.E.S.T. term available up to 36 months | |



