

2026 OUTLANDER MAX XT



Platinum Satin
Dark Wildland Camo
Fiery Red

PACKAGE HIGHLIGHTS

850	1000R
<ul style="list-style-type: none">• Tri-Mode Dynamic Power Steering (DPS™)• Intelligent Engine Braking (iEB™) and driving modes• Radiator cooling fan of 80W & 150 cm³• Visco-Lok[†] QE auto-locking front differential• 26 in. XPS Trail King 2 dedicated trail tires• 14 in. aluminum wheels• 3,500 lb winch with synthetic rope• 7.6 in. wide digital display• Full skid plate, front bumper, rear bumper• Phone storage and USB charger• Front drop-down storage• Rear removable storage	850 package highlights plus 1000R exclusive features: <ul style="list-style-type: none">• Visco-4Lok[†]• Specific CVT calibration• High flow radiator cooling fan of 120W & 500 cm³• 4-disc braking system• Front sway bar• LED signature lights• Extra painted panels

ENGINES	850	1000R
Type	82 hp / 66 lb-ft, Rotax® 999 cc V-twin, DOHC, liquid-cooled Radiator cooling fan of 80W & 150 cm³	101 hp / 69 lb-ft, Rotax 999 cc V-twin, DOHC, liquid-cooled High flow radiator cooling fan of 120W & 500 cm³
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	
Transmission	pDrive primary CVT L / H / N / R / P	pDrive primary CVT with specific calibration L / H / N / R / P
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential	Selectable 2WD / 4WD / Lock 4WD with Visco-4Lok [†] front differential
Driving Assistance	Work / Standard / Sport modes Intelligent Engine Braking (iEB)	
Power Steering	Tri-Mode Dynamic Power Steering (DPS)	
SUSPENSIONS		
Front Suspension	Arched double A-arm 10.8 in. (27.4 cm) travel	Arched double A-arm with sway bar 10.8 in. (27.4 cm) travel
Front Shocks	Twin-tube	
Rear Suspension	Arched double A-arm 12 in. (30.5 cm) travel	
Rear Shocks	Twin-tube	
TIRES & WHEELS		
Front / Rear Tires	XPS Trail King 2 – 26 x 8/10 x 14 in.	
Wheels	14 in. aluminum	
BRAKES		
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers	
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper	Dual 214 mm disc brakes with hydraulic twin-piston calipers

DIMENSIONS & CAPACITIES

	850	1000R
Estimated Dry Weight*	998 lb (453 kg)	
L x W x H	99 x 48.5 x 56.4 in. (252 x 123.2 x 143.2 cm)	
Wheelbase	60.8 in. (154.4 cm)	
Ground Clearance	11.5 in. (29.2 cm)	
Seat Height	37.8 in. (96 cm)	
Rack Capacity	Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg)	
Storage Capacity	10.6 gal (40 L)	
Towing Capacity	1,830 lb (830 kg)	
Fuel Capacity	5.1 gal (19.5 L)	

FEATURES

Gauge	7.6 in. wide digital display	
Magneto	650 W	
Instrumentation	Phone storage & USB-C charger	
Ignition	RF Digitally Encoded Security System (D.E.S.S.™)	
Lighting	LED headlights and taillights	LED headlights and taillights LED signature
Winch	Can-Am HD3500 (1,588 kg) winch with synthetic cable	
Seat	Removable passenger seat	
Handlebar	Standard	
Protection	Full skid plate Heavy-duty front and rear bumpers Handguards	
Hitch Type	2 in. hitch receiver	

WARRANTY & EXTENDED SERVICE

Factory Warranty	1-year BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 36 months

can-am

© 2025 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in the U.S.A. call the ATV Safety Institute at 1-800-887-2887. In Canada, call the Canadian Safety Council at 1-613-739-1535, ext 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding, alcohol and drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90 cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

A BRP BRAND

